

HYDRAULIC
FLUID



PENTOSIN CHF 7.1

Mineral Oil-Based Hydraulic Fluid For Older Vehicles

DESCRIPTION

Pentosin CHF 7.1 is a high performance hydraulic fluid, formulated with mineral base oils, for life-time lubrication in older/vintage vehicle aggregates. It serves in power steering systems, shock absorber, automatic level control and other chassis suspension systems. Pentosin CHF 7.1 is NOT miscible with modern high performance hydraulic fluids such as the Pentosin CHF 11S or CHF 202.

PRODUCT ATTRIBUTES

Appearance	Green
Density at 20°C	845 kg/m ³
Kinematic Viscosity at 100°C	6.2 mm ² /s
Kinematic Viscosity at 40°C	18.6 mm ² /s
Kinematic Viscosity at -40°C	1100 mm ² /s
Viscosity Index	340
Pour Point	-54°C/-65.2°F
Flash Point	130°C/266°F
Ignition Temperature	245°C/473°F

SIZE	PART NUMBER	GTIN-13
1 Liter	1404106	4008849504013

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi/Volkswagen	AOE 041 020 10
BMW	81 22 9 407 549
BMW	81 22 1 468 879
Volvo	11 61 317

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
BMW	81229407549
DIN	51 524 T3
ISO	7308

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional installer upon request.