



PENTO SUPER PERFORMANCE III 5W-30

Fully Synthetic Extended Life Engine Oil

DESCRIPTION

Pento Super Performance III 5W-30 is a newly formulated high performance engine oil that provides extended oil drain intervals in modern engines. Using state-of-the-art additive technology and synthetic base oils, a “low SAPS” oil (“low ash generating oil”) was blended in a way that preserves the catalyst and environment while maintaining outstanding engine performance.

PRODUCT ATTRIBUTES

Appearance	Brown
Density at 15°C	852 kg/m ³
Kinematic Viscosity at 100°C	11.9 mm ² /s
Kinematic Viscosity at 40°C	71.3 mm ² /s
Viscosity Index	166
Dynamic Viscosity at -30°C	5900 mPa*s
Pour Point	-39°C/-38.2°F
Flash Point	230°C/446°F

SIZE	PART NUMBER	GTIN-13
1 Liter	8078106	4008849115431
5 Liter	8078206	4008849115448
20 Liter	1078208	4008849115301
60 Liter	1078303	4008849111563
210 Liter	1078305	4008849111761

OE REFERENCE NUMBERS

Make	Reference Number
Audi/Volkswagen	G 052 195 M2
Audi/Volkswagen	G 052 195 M4
Audi/Volkswagen	G 052 195 M6
BMW	83 21 0 398 507
BMW/MINI	83 21 0 398 508
Mercedes-Benz	000 989 89 01 10

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Audi/Volkswagen	504.00, 507.00
BMW	LL-04
Mercedes-Benz	229.51
ACEA	C3
API	SN
Porsche	C30

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© 2016 CRP Industries Inc. Pentosin is a trade name of Deutsche Pentosin-Werke. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOSP115W30-060116



OE-quality brands for import applications.