

TRANSMISSION
FLUID



PENTOSIN ATF 134 FE

Premium Performance, Low Viscosity Automatic Transmission Fluid

DESCRIPTION

Pentosin ATF 134 FE was developed to further optimize gearbox efficiency of the latest generation Mercedes-Benz 7-G Tronic Plus (NAG II+) automatic transmissions. This advanced OEM Approved fluid is the lowest viscosity ATF available in the world, providing impressive fuel economy potential and low temperature performance. **IMPORTANT NOTE: Pentosin ATF 134 FE is NOT downwards compatible with previous MB-ATF specifications.**

PRODUCT ATTRIBUTES

Appearance	Blue
Density at 15°C	0.841 g/ml
Flash Point	190°C/374°F
pH Value	N/A
Dynamic	N/A
Kinematic Viscosity at 40°C	18 mm ² /s
Viscosity Index	160

SIZE	PART NUMBER	GTIN-13
1 Liter	1089117	4001541459209
5 Liter	1089216	4001541459216

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Mercedes-Benz	001989780309

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Mercedes-Benz	236.15

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of Deutsche Pentosin-Werke. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOATF134FE-0317



OE-quality brands for import applications.