

TRANSMISSION
FLUID



PENTOSIN ATF 8

Long-Life Fully Synthetic Automatic Transmission Fluid

DESCRIPTION

Pentosin ATF 8 has been specially developed with reduced viscosity to optimize the performance of specified 6 and 8-speed ZF automatic transmissions. Due to the individual design and technical requirements each transmission needs to achieve, it is essential the correct ATF is specified in order to ensure the transmission performs to its potential, providing efficient and reliable operation throughout its lifetime. Pentosin ATF 8 has been developed to be suitable for use with a range of automatic transmissions and delivers improved friction control, strong anti-shudder performance along with excellent oxidation performance and wear protection.

PRODUCT ATTRIBUTES

Appearance	Green
Density at 15°C	0.843 g/ml
Kinematic Viscosity at 100°C	6.0 mm ² /s
Kinematic Viscosity at 40°C	28.3 mm ² /s
Viscosity Index	166
Pour Point	-42°C/-43.6°F
pH Value	Slightly Alkaline

SIZE	PART NUMBER	GTIN-13
1 Liter	1058110	4001541229529
5 Liter	1058210	4001541229536

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi/Volkswagen	G 055 162 (Blue)
Audi/Volkswagen	G 060 162 A2/A6 (Green)
BMW	83222289720 (ATF3+)
Chrysler	68157995AA
Jaguar	02JDE 26444
Land Rover	LR023288
ZF	S671 090 312

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Asian Vehicles	JASO M315 TYPE 1A-LV

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of FUCHS Schmierstoffe GmbH. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOATF8-090519



OE-quality brands for import applications.