

TRANSMISSION FLUID



PENTOSIN FFL-2

Fully Synthetic Double Clutch (DSG) Transmission Fluid

DESCRIPTION

Pentosin FFL-2 is the only approved first fill and service fill transmission fluid for the new generation of AVW double clutch gear transmissions (DSG). Pentosin FFL-2 is founded on a fully synthetic base oil technology for safe operation at even the highest thermal load. FFL-2 features a special clutch friction performance which makes it mandatory to be applied solely to the double clutch gear box – do not mix with any other gear oils.

PRODUCT ATTRIBUTES

Appearance	Amber & Clear
Density at 15°C	845 kg/m ³
Density at 20°C	841 kg/m ³
Kinematic Viscosity at 40°C	36.3 mm ² /s
Viscosity Index	173
Dynamic Viscosity at -40°C	12100 mPa*s
Pour Point	-51°C/-59.8°F
Flash Point	224°C/435.2°F
pH Value	N/A

SIZE	PART NUMBER	GTIN-13
1 Liter	1038107	4008849174216
5 Liter	8038207	4008849113222
20 Liter	1038208	4008849172212

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi/Volkswagen	G 052 182 A2
Audi/Volkswagen	G 052 182 A6

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Audi/Volkswagen	TL 521 82

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© CRP Industries Inc. Pentosin is a trade name of Deutsche Pentosin-Werke. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions, or manufacturing changes.

PENTOFFL2-121217



OE-quality brands for import applications.